

RUBBER SHEETING

WEAR RESISTANT RUBBER

Natural Rubber Sheeting NR

Recommended for the mining of quarrying industries and any other applications exposed to abrasive materials.

- ✓ Primarily used for reducing abrasión and dust problems although also noise levels in the plant.
- ✓ High elasticity. Excellent mechanical and dynamics properties.
- ✓ Wide range of hardness: 35 to 90° Shore A
- ✓ Temperature range: -50° / 85° C

Applications: Quarries, mines, gravels and other processed industries.



GD 60

Used primarily for protection from wear and corrosion in chutes, hoppers, washer cylinders...



GC 45

Available for conveyor skirting, sealing rubber and concrete discharge.



GE 45

Specially created for the protection system against dust emissions.



GV 50

Primarily used as a skirting rubber for the protection on sides of conveyor belt.



GS Sandwich

Recommended as a belt scraper for his cleaning.



GR 60

Used for lagging of drums. Same quality than **GD60** rubber but with diamond shape.



GA 60

Steel-backed rubber sheets. Same **GD60** rubber quality. Excellent results against high impact and cut resistance.

GK 60

Rubber sheet with adhesive on one side for cold vulcanized in chutes, hoppers... Same **GD60** rubber quality. Reduced installation cost.

(See other wear rubber available by request)